## (12) 按照专利合作条约所公布的国际申请

#### (19) 世界知识产权组织 国际局

### (43) 国际公布日: 2005年1月6日(06.01.2005)



**PCT** 

# 

(10) 国际公布号: WO 2005/000451 A1

(51) 国际分类号7:

B01D 53/80, 53/18, B01J 8/00

(21) 国际申请号:

PCT/CN2003/000862

(22) 国际申请日:

2003年10月16日(16.10.2003)

(25) 申请语言:

中文

(26) 公布语言:

中文

(30) 优先权:

03148026.8

2003年6月30日(30.06.2003)

CN

层, Beijing 100027 (CN)。

(81) 指定国(国家): DE, JP, US

包括国际检索报告。

本国际公布:

(71)(72) 发明人/申请人: 史汉祥(SHI, Hanxiang) [CN/CN]; 中国浙江省慈溪市宗汉镇史家村, Zhejiang 315301 (CN).

所引用双字母代码和其它缩写符号, 请参考刊登在每期 PCT公报期刊起始的"代码及缩写符号简要说明"。


(74) 代理人: 北京邦信阳专利商标代理有限公司(BOSS &


OFFICE), 中国北京市朝阳区霄云路36号国航大厦9

YOUNG PATENT & TRADEMARK LAW

(54) Title: A MULTIPHASE REACTOR

(54) 发明名称: 一种多相反应器





(57) Abstract: This invention relates to a multiphase reactor which is especially suitable in the desulfurization of flue gas. Inside the multiphase reactor housing fixed a rotary build-in member, which comprises an axisymmetric body and an annular body. axisymmetric The housing cylindrical, and its surface is smooth or waved. The axisymmetric body, which is set above the annular axisymmetric body coaxially, has a maximal diameter not less than the inner diameter of the annular axisymmetric body. One rotary build-in member and its housing constitute a unit, and a multiphase reactor can have one or more such units. The multiphase reactor according to this invention could improve the liquid flow pattern sufficiently, prevent the solid deposition, make gas, liquid and solid phases contact substantially, and enhance the mass transfer velocity; and it has a simple structure, is convenient for use, especially suitable for use in environmental protection, chemical engineering, metallurgical and architectural industries. It has a rotary build-in member.

WO 2005/000451

#### (57) 摘要

本发明涉及一种多相反应器,它尤其适用于二氧化硫烟气脱硫。其内由旋转体和环型旋转体组合成的旋转体式内置构件结构固定在多相反应器壳体上。其壳体是圆筒形,圆筒的表面是光滑的或是波浪形的;其旋转体的最大直径不小于环型旋转体内环直径,旋转体在环型旋转体上方,两者是同轴的。一个旋转体式内置构件和相应的壳体构成一个单元,一个多相反应器可由一个单元构成,也可多个单元构成。本多相反应器能有效改善流体流型,固相不易沉积,气液固三相接触充分,强化传质速率,且结构简单,使用方便、适用于环保、化工、冶金、建材等行业。设置有旋转体式内置构件。